

Product Specification

10/100M Unmanaged Industrial Ethernet Switches (FLD-S-1F1F-I)

Introduction	Image
<p><i>This industrial media converter is specially designed for industrial application, which provides fast and stable media conversion between 10/100BaseTX and 100BaseFX. It also meets the requirements of long distance, high speed, and wide broadcast.</i></p> <p><i>With wide range operation temperature, alloy aluminum shell and other excellent industrial-grade design against vibration and shock, it could keep your industrial automation applications running continuously in different harsh environments.</i></p>	 <p>The image shows a black industrial Ethernet media converter with a blue front panel. It features a TPI Ethernet port and an FXI fiber optic port. Below the device are three certification logos: CE, FCC, and RoHS.</p>

Features & Benefits
❖ 1 10/100Base-T(X) ports and 1 100Base-FX port
❖ -40°C-85°C operating temperature range
❖ Super lightning protection, IP40 protection
❖ Excellent heat elimination without cooling fan

Physical Characteristics
❖ Housing: Aluminum Alloy material with IP40 Protection
❖ Dimension: 138mm(L) X 112mm(W) X 42mm(H)
❖ Weight: 480g
❖ Installation: Din-Rail mounting, Wall mounting

Switch Properties

- ❖ MAC Table Size: 2K
- ❖ Packet Buffer Size: 1M bit
- ❖ Processing Type: Store and Forward
- ❖ Exchange Properties: 148800pps (100M)

Interfaces

- ❖ 1 100Base-FX port (SC/ST/FC/LC connectors optional)
- ❖ 1 RJ45 Ports: 10/100Base-T(X) auto negotiation

Power

- ❖ Input Voltage: 24V DC(18-36VDC) Redundant dual inputs
- ❖ Input Current: <0.5A @24VDC
- ❖ Overload Current Protection: Present
- ❖ Reverse Polarity Protection: Present
- ❖ Redundant Protection: Present

Environmental Limits

- ❖ Operating Temperature: -40°C-85°C
- ❖ Storage Temperature: -40°C-85°C
- ❖ Ambient Relative Humidity: 5%-95% (non-condensing)

Standards

- ❖ EMS:
 - EN61000-4-2 (ESD), Level 3
 - EN61000-4-3 (RS), Level 3
 - EN61000-4-4 (EFT), Level 3
 - EN61000-4-5 (Surge), Level 3
 - IEC61000-4-8(100A/m), Level 3
 - IEC61000-4-11, Level 3
- ❖ Shock: IEC 60068-2-27
- ❖ Free Fall: IEC 60068-2-32

FIBERLAND

Fiber Optic & Networking Products


Let's create a pure fiberland for human beings

❖	Vibration: IEC 60068-2-6
❖	EMI: FCC CFR47 Part 15, EN55022/CISPR22, Class A
❖	Industry: IEC61000-6-2
❖	Rail: EN50155, EN50121-4
❖	Traffic: NEMA TS-2

Warranty

5 years

Dimension : FLD-S-1F1F-I



Contact :

Address	6 th floor ,building 8,Zhongxing industrial zone,Nanshan district,Shenzhen,P.R.China
Zip	518000
Website	www.fiberlandtec.com
Email	sales@fiberlandtec.com